

QUERY CONTROL FORM			RTIS USE ONLY		
Application No.	<u>10/081,396</u>	Prepared by	<u>Lois Stone</u>	Tracking Number	<u>871514</u>
Examiner-GAU	<u>Lee - 3874</u>	Date	<u>1/9/04</u>	Week Date	<u>12/8/03</u>
		No. of queries	<u>1</u>	IFW	

JACKET

a. Serial No.	f. Foreign Priority	k. Print Claim(s)	p. PTO-1449
b. Applicant(s)	g. Disclaimer	l. Print Fig.	q. PTOL-85b
c. Continuing Data	h. Microfiche Appendix	m. Searched Column	<u>r. Abstract</u>
d. PCT	i. Title	n. PTO-270/328	s. Sheets/Figs
e. Domestic Priority	j. Claims Allowed	o. PTO-892	t. Other

SPECIFICATION

- a. Page Missing
- b. Text Continuity
- c. Holes through Data
- d. Other Missing Text
- e. Illegible Text
- f. Duplicate Text
- g. Brief Description
- h. Sequence Listing
- i. Appendix
- j. Amendments
- k. Other

CLAIMS

- a. Claim(s) Missing
- b. Improper Dependency
- c. Duplicate Numbers
- d. Incorrect Numbering
- e. Index Disagrees
- f. Punctuation
- g. Amendments
- h. Bracketing
- i. Missing Text
- j. Duplicate Text
- k. Other

MESSAGE

Please provide a copy of the abstract.

Thank you,

initials cas

RESPONSE See Copy attached.

initials

ABSTRACT OF THE DISCLOSURE

5 An optical router integrated in an InP-based substrate bonded to a single thermo-electric cooler for packet-based networks utilizing wavelength-division multiplexing (WDM) on silica fibers. Input and output arrayed waveguide gratings (AWGs) respectively demultiplex and multiplex the WDM signals to and from multiple transmission fibers. Input and output wavelength converters are connected between the input and outputs AWGs and a switching AWG. The output converts may include a tunable laser and interferometer formed in the same substrate. The header information is preferably carried out-of-channel from the WDM data signals, either in the same fiber band or a different one. Photodetectors and laser diodes are formed in the same substrate. Fast RF electronics are formed in GaAs chips and slower electronics formed in a silicon chip are bonded to the InP wafer